



ATEX

The MX series of Gefran, are pressure transmitters for using in High temperature environment. The main characteristic of this series is the capability to read temperature of the media up to 400°C. The constructive principle is based on the hydraulic transmission of the pressure. The fluid-filled system assures the temperature stability. The physical measure is transformed in a electrical measure by means the strain-gauge technology.

MAIN FEATURES

- Pressure ranges: 0-17 to 0-2000bar / 0-250 to 0-30000psi
- Extensimetric measurement principle with Wheatstone bridge
- Precision: $\pm 0.25\%$ FS (H); $\pm 0.5\%$ FS (M)
- Calibration signal 80% FS internally generated
- Completely interchangeable with all existing products
- Protection level: IP65 (6-pin connector)
- Standard threading 1/2-20UNF, M18x1.5, other versions on request
- Stainless steel diaphragm 15-5 PH with GTP+ coating
- For ranges below 100 bar-1500 psi: 17-7 PH corrugated stainless steel diaphragm with GTP+ coating
- Other diaphragm types available on request

MX0 The rigid rod configuration provides fast and easy installation.

MX1 The flexible rod configuration is suitable for applications demanding greater thermal isolation and where installation would otherwise be difficult.

MX2 This configuration lets you measure process pressure and temperature at the same point with a single installation.

MX3 The configuration with exposed tip is ideal for applications in limited space.

MX4 Flange configuration for specific applications

Main intrinsic safety characteristics

Transmitter designed and produced in compliance with Directive ATEX 2014/34/EU and according to European standards: for the second group (II-surfaces), category 1, explosive atmosphere with presence of gases, fumes or mists (G) protection mode Ex ia IIC T5, T4 room temperature -20°C/+55°C/+60°C/+70°C

Maximum voltage	30 V
Maximum current	100 mA
Maximum power	0,75 W
Equivalent inductance (*)	0,23 mH
Equivalent capacity (*)	26 nF

(*) includes inductance levels and capacity of a cable: (typical L 1microH/m and typical C 100pF/m) with maximum length 15m.

TECHNICAL SPECIFICATIONS

Accuracy (1)	H $\pm 0,25\%$ FS (100...2000 bar) M $\pm 0,5\%$ FS (17...2000 bar)
Resolution	Infinite
Pressure ranges	0..17 a 0..2000bar 0..250 a 0..30000psi
Maximum applicable pressure	2 x FS 1,5 x FS oltre i 1000bar/15000psi
Principle of measurement	Strain gauge
Power supply	12..30Vdc
Maximum input	30mA
Isolation resistance (at 50 Vdc)	>1000 MΩ
Signal at rated pressure (FS)	20mA
Zero balancing	4mA
Calibration:	Rated pressure Room pressure
	5% FS min. 10bar (150psi)
Maximum load	see diagram (page 3)
Response time (10 at 90% FS)	~ 4ms
Output noise (RMS 10-400Hz)	< 0,05% FS
Calibration signal	80% FS
Protection against overvoltages and power supply polarity reverse	SI
Temperature range of Strain Gauge	-20...+70°C
Housing	-4...+158°F
Thermal drift in compensated range: Zero/Calibrat/Sensitivity	< 0,02% FS/°C < 0,01% FS/°F
Maximum temperature of diaphragm	400°C / 750°F
Influence due to fluid temperature change (zero)	0,02 bar/°C 15 psi/100°F
Standard material in contact with process medium	Diaphragm: • 15-5 PH with GTP+ coating • 17-7 PH corrugated diaphragm with GTP+ coating for ranges <100 bar (1500psi) Stem: • 17-4 PH
Thermocouple (model MX2)	STD: type "J" (isolated junction)
Protection level (with 6-pin female connector installed)	IP65
Electrical connections	6-pin conn. VPT07RA10-6PT (PT02A-10-6P) 8-pin conn. PC02E-12-8P

FS = Full Scale Output (Signal at rated pressure)


Power at zener barrier or active barrier. For version MX2, the thermocouple must be connected to EX-i circuits with devices assigned to galvanic separation and with protection mode [EX ia] IIC.



EC-Type Examination Certificate number:
CESI 02 ATEX 107

MECHANICAL DIMENSIONS


MX0



MX2

D1	1/2 - 20UNF
D2	ø7.8 -0.05 [ø0.31" -0.002]
D3	ø10.5 -0.025 [ø0.41" -0.001]
D4	ø10.67 [ø0.42"]
D5	ø12.7 [ø0.5"]
A	5.56 -0.26 [0.22" -0.01]
B	11.2 [0.44"]
C	15.74 [0.62"]
Ch [Hex]	16 [5/8"]

MX1



MX3


D1	M18x1.5
D2	$\varnothing 10$ -0.05 [$\varnothing 0.394"$ -0.002]
D3	$\varnothing 16$ -0.08 [$\varnothing 0.63"$ -0.003]
D4	$\varnothing 16$ -0.4 [$\varnothing 0.63"$ -0.016]
D5	$\varnothing 18$ [$\varnothing 0.71"$]
A	6 -0.26 [$0.24"$ -0.01]
B	14.8 -0.4 [$0.58"$ -0.016]
C	19 [$0.75"$]
Ch [Hex]	19 [$3/4"$]

Exposed capillary	
D1	1/2-20UNF
D2	.307/.305" [7.80/7.75mm]
D3	.414/.412" [10.52/10.46mm]
A	.145/.151" [3.68/3.84mm]
B	.318/.312" [8.08/7.92mm]
C	.81" [20.6mm]

NOTE : dimensions refer to rigid stem length option "4" (153 mm - 6")

WARNING : For installation use a maximum tightening torque of 56 Nm(500 in-lb)

MX4




ELECTRICAL CHARACTERISTICS AND TEMPERATURE CLASSES


MODEL	(*) LEVEL L2	(*) LEVEL L1	TEMPERATURE CLASSES	ROOM TEMPERATURE
MX0	>165mm	>125mm	T4	-20...+60°C
MX1	>665mm	>625mm	T5	-20...+55°C
			T4	-20...+70°C
MX2	>665mm	>625mm	T5	-20...+55°C
			T4	-20...+70°C
MX3	>665mm	>625mm	T5	-20...+55°C
			T4	-20...+70°C
MX4	>785 mm	-	T5	-20...+55°C
			T4	-20...+70°C

(*) with the level (L) in fig. 1, the table sets the minimum distance that the electrical circuit has to maintain from the block at high temperature.

MX0 - MX1 - MX2 - MX3



MX4



thermal isolating material with adequate thickness for the process temperature

pressure transmitter housing block

fluid at temperature Max. (400°C)

thermal isolating material with adequate thickness for the process temperature

installation Vs process

fluid at temperature Max. (400°C)


ELECTRICAL CONNECTIONS

Output in current (4...20mA 2 wires)


	6-pin	8-pin
Power supply (12...30Vdc)	+	A B
	n.c.	C A
Signal (4...20mA)	-	B D
	n.c.	D C
Calibration shunt	E - F	E - F
	n.c.	G - H

The cable sheathing is connected to the transducer body


6 pin connector
VPT07RA10-6PT2
(PT02A-10-6P)



8 pin connector
PC02E-12-8P Bendix




LOAD DIAGRAM (current output)



The diagram shows the best ratio of load to power supply for transmitters with 4...20mA output. For correct function, use a combination of load resistance and voltage that stays in the shaded zone.

SETTINGS



The signal setting to room pressure (ZERO) and the setting to rated pressure (SPAN) can be made with the appropriate trimmers, accessed inside the transmitter after removing the two fastening screws.

The SPAN setting is made during production and must not be changed.

Accessories

- Fastening bracket
- Silver-plated copper washer
- Protection plug for 1/2-20 UNF
- Protection plug for M18x1.5
- Drill kit for 1/2 -20 UNF
- Drill kit for M18 x 1.5
- Cleaning kit for 1/2-20 UNF
- Cleaning kit for M18x1.5

- SF18**
- RON007**
- SC12**
- SC18**
- KF12**
- KF18**
- CT12**
- CT18**

Extension cables

- 6-pin connector with 3mt Atex cable
- 6-pin connector with 4mt Atex cable
- 6-pin connector with 5mt Atex cable
- 6-pin connector with 10mt Atex cable

- PCAV221**
- PCAV104**
- PCAV105**
- PCAV106**

Thermocouples for model MX2

- Type "J" (for rigid rod 153mm - 6")

- TTER 718**


PROCESS FLANGE ADAPTER

The process flange adapter is a sensor accessory that allows for the installation of 1/2-20 UNF or M18x1.5 melt pressure sensor in a button seal style process mounting port. The adapter is made with an adapter body with different snout lengths plus an adapter flange available in different sizes (see tables and drawing below). Each combination of snout and flange is available according to the ordering information with a specific ordering code.

SPECIFICATIONS

- Pressure range: according to the selected sensor (up to 1000 bar/15000 psi max)
- Temperature range: according to the selected sensor
- Material of construction: 17-4PH Stainless steel


ADAPTER BODY



1/2-20 UNF	L - SNOUT LENGTH
STE1020	127 [5]
STE1021	51,6 [2,031]

M18 X 1,5	L - SNOUT LENGTH
STE1022	127 [5]
STE1023	51,6 [2,031]

ADAPTER FLANGE



	FLA960	FLA961
D_1	82,6 [3,25]	88,9 [3,50]
D_2	54 [2,14]	63,5 [2,50]
D_3	13,2 [0,52]	14,3 [0,56]
D_4	5/16-18 UNC	5/16-18 UNC

ORDER CODE

KIT	5	0	1
Snout length			
5 inch [127 mm]	5		
2,031 inch [51,6 mm]		2	
Flange type (see technical drawing)			
FLA960	0		
FLA961		1	
Thread dimensions			
1/2-20 UNF	1		
M18 x 1,5		4	

ADAPTER GASKESTS			
Material	Dimensions	Max Pressure	Ord. Code
Aluminium	30.2 mm [1.19"] OD 24.1 mm [.950"] ID	200 bar/3000 psi	RON360
AISI 303 SS	30.2 mm [1.19"] OD 24.1 mm [.950"] ID	700 bar/10000 psi	RON361

Example:

KIT501

Process adapter with 5" snout length, 82.6 mm size flange, suitable for 1/2-20 UNF melt sensor

ORDER CODE

OUTPUT SIGNAL		4...20mA	X
CONFIGURATION			
Rigid rod	0		
Rigid rod + flexible	1		
With thermocouple	2		
Exposed tip	3		
Flange assembly	4		
CONNECTOR			
Standard			
6 pin	6		
8 pin	8		
PRECISION CLASS			
0,25% FS (ranges \geq 100 bar/1500 psi)	H		
0,5% FS	M		
MEASUREMENT RANGE			
bar		psi	
17	B17U	250	P25D
35	B35U	500	P05C
50	B05D	750	P75D
70	B07D	1000	P01M
100	B01C	1500	P15C
200	B02C	3000	P03M
350	B35D	5000	P05M
500	B05C	7500	P75C
700	B07C	10000	P10M
1000	B01M	15000	P15M
1400	B14C	20000	P20M
2000	B02M	30000	P30M

Notes:
the models MX0/MX1/MX3 are available in a special version XM3GD realized to work in the presence of gases (zone 2) and powders (zone 22).

Marking:  II 3G Ex ec IIC T4,T5,Gc
II 3D Ex tc IIIC T135°C,T100°C Dc,IP65

Examples:

MX1-6-M-B05C-1-4-D-5-(XM3GD)

Example

MX1-6-M-B07C-1-4-D-4-000

Melt pressure transducer with flexible rod, 4...20mA output, 6-pin connector, fi-20 UNF threading, pressure range 700 bar, precision class 0.5%, 153 mm (6") rigid rod, 457 mm (18") flexible rod, temperature class T4

Sensors are manufactured in compliance with:

- EMC compatibility directive: 2014/30/EU
- ATEX directive: 2014/34/EU

Product designed and available in compliance with Directive 2011/65/EU (RoHS II) only for large-scale stationary installation or industrial tools, or for B-to-B laboratory equipments for R&D purposes.

Electrical installation requirements and Conformity certificate are available on our web site: www.gefran.com

GEFRAN spa reserves the right to make aesthetic or functional changes at any time and without notice.

GEFRAN spa

via Sebina, 74

25050 PROVAGLIO D'ISEO (BS) - ITALIA

tel. +39 030 9888.1 - fax. +39 030 9839063

<http://www.gefran.com>

000= Special executions of the standard version or of custom versions may be requested.

4	T4
5	T5

NOTES: Series MX0 available only in T4 class

FLEXIBLE ROD LENGTH
(mm / inches)

Standard (MX0)

0	none
---	------

Standard (MX1, MX2)

D	457mm	18"
E	610mm	24"
F	760mm	30"

Standard (MX1, MX2)

L	711mm	28"
---	-------	-----

Available on request

A	76mm	3"
B	152mm	6"
C	300mm	12"
G	914mm	36"
H	1067mm	42"
I	1220mm	48"
J	1372mm	54"
K	1520mm	60"

RIGID ROD LENGTH
(mm / inches)

Standard (MX0, MX1, MX2)

4	153mm	6"
5	318mm	12.5"

Standard (MX3)

0	nessuno
---	---------

Available on request

1	38mm	1.5"
2	50mm	2"
3	38mm	3"
6	350mm	14"
7	400mm	16"
8	456mm	18"

Standard (MX4)

4	153mm	6"
---	-------	----

Available on request

H	102mm	4"
M	229mm	9"
5	305mm	12"

THREADING

Standard

1	1/2 - 20 UNF
4	M18 x 1.5
6	Flange assembly ø 66.3mm (2.61")