



FE3303 EX proof Sanitary Flow Sensor Stainless Steel Housing Seal Plus structure Connection: External thread G1 Programmable 3 digit display M12 socket	
Ex-proof marking	Ex nA IIC T4 Gc / Ex tD A21 IP67 T100°C
Applications	Liquid and gas
Electric design	DC Relay
Supply voltage[V]	20...36 DC
Output	NO  NC 
Reverse polarity protection	Yes
Current consumption[mA]	<80
Max. temperature drift[K/min]	300
Pressure resistance[bar]	30
Liquid setting range[cm/S]	3...300
Max sensitivity of range for liquid[cm/S]	3...100
Gas setting range[cm/S]	200...3000
Max sensitivity of range for gas[cm/S]	200...800
Startup time[s]	< 8
Output response time[s]	< 2
Medium temperature[°C/°F]	-25...95/-13...203 (140°C 1H)
Environment temperature[°C/°F]	-25...80/-13...176
Storage temperature[°C/°F]	-25...100/-13...212
Protection/Enclosure Rating	IP67/IP69K*
Certification	FDA
ESD EN61000-4-2	6kV-CD / 8kV-AD
EFT EN61000-4-4	2kV
Surge immunity	1kV
Walkie talkie experiment[mm]	<10
Shock resistance[g]	50
Vibration resistance[g]	20
Upper cover material	Stainless steel 316L
Lower cover material	Stainless steel 304
Probe material/Wetted Parts	Stainless steel 316L
Connection	M12 socket

Dimensions[mm]	
Wiring Core color Pin 1=BN Pin 2=WH Pin 3=BU Pin 4=BK Pin 5=RD	
Note*	Use sanitary adapter to upgrade to IP69K (Optional accessory)



Akdeniz Mekatronik San.Tic.Ltd.Şti
Yeşiloba Mahallesi 46290 Sk. No:4 Adana/Türkiye
Tel. +90 322 428 11 44
E-mail: info@akdenizmekatronik.com.tr