


FE6205 EX proof Electronic Flow + Temp Sensor Stainless Steel Housing Seal Plus structure Connection: Internal thread M18 x 1.5 Programmable M12 socket	
Ex-proof marking	Ex nA IIC T4 Gc / Ex tD A21 IP67 T100°C
Applications	Liquid and gas
Electric design	DC 2 x 4-20 mA
Supply voltage[V]	20...36 DC
Reverse polarity protection	是
Current consumption[mA]	<80
Programming options	Window function, Output setting, High/Low switching point setting, °C/°F, Unit display
Max. temperature drift[K/min]	300
Pressure resistance[bar]	30
Liquid temperature[°C/°F]	-25...80/-13...176
Liquid setting range[cm/S]	3...300
Max sensitivity of range for liquid[cm/S]	3...100
Gas temperature[°C/°F]	-25...80/-13...176
Gas setting range[cm/S]	200...3000
Max sensitivity of range for gas[cm/S]	200...800
Startup time[s]	< 8
Output response time[s]	< 2
Ambient temperature[°C/°F]	-25...80/-13...176
Protection/Enclosure Rating	IP67
Dimensions[mm]	

ESD EN61000-4-2	6kV-CD / 8kV-AD
EFT EN61000-4-4	2kV
Walkie talkie experiment[mm]	< 10
Shock resistance[g]	50
Vibration resistance[g]	20
Upper cover material	Stainless steel 316L
Lower cover material	Stainless steel 304
Probe material/Wetted Parts	Stainless steel 316L
Function Display	Flow : 10 x 3 colors LED
Connection	M12 socket
Wiring	
Core color	
Pin 1=BN	
Pin 2=WH	
Pin 3=BU	
Pin 4=BK	
Pin 5=RD	



Akdeniz Mekatronik San.Tic.Ltd.Şti
Yeşiloba Mahallesi 46290 Sk. No:4 Adana/Türkiye
Tel. +90 322 428 11 44
E-mail: info@akdenizmekatronik.com.tr