



FL6401 Remote Flow Sensor Control Monitor Stainless Steel Housing Seal Plus structure External thread G1/2"A Programmable M12 socket	
Applications	Liquid and gas
Electric design	PNP NO/NC
Supply voltage[V]	20...36 DC
Output	NO  NC 
Max. overload current[mA]	400
Reverse polarity protection	Yes
Overload protection	Yes
Watchdog	Yes
Max. overload current[mA]	<80
Max. temperature drift[K/min]	300
Pressure resistance[bar]	300
Liquid temperature[°C/°F]	-25...80/-13...176
Liquid setting range[cm/S]	3...300
Max sensitivity of range for liquid[cm/S]	3...100
Gas temperature[°C/°F]	-25...80/-13...176
Gas setting range[cm/S]	200...3000
Max sensitivity of range for gas[cm/S]	200...800
Startup time[s]	< 8
Output response time[s]	< 2
Ambient temperature[°C/°F]	-25...80/-13...176
Protection/Enclosure Rating	IP68
Dimensions[mm]	
ESD EN61000-4-2	6kV-CD / 8kV-AD
EFT EN61000-4-4	2kV
Shock resistance[g]	50
Vibration resistance[g]	20
Upper cover material	Stainless steel 316L
Housing material	Stainless steel 304

Function Display	Flow : 10 x 3 colors LED
Connection	M12 socket
Wiring	 NO/NC NO or NC setting via the menu
Core color	
Pin 1=BN	
Pin 2=WH	
Pin 3=BU	
Pin 4=BK	
Pin 5=RD	



Akdeniz Mekatronik San.Tic.Ltd.Şti
Yeşiloba Mahallesi 46290 Sk. No:4 Adana/Türkiye
Tel. +90 322 428 11 44
E-mail: info@akdenizmekatronik.com.tr