


LE0106
EX proof High-Frequency Level Switch
RELAY output
High-temperature + Extension type
L=250mm
G1/2"A thread
M12*1.0 socket



Auto-learning function
For powder,liquid,sticky liquid



Ex-proof marking	Ex nA IIC T5 Gc / Ex tD A21 IP67 T100°C
Application	Powder,liquid, suitable for sticky liquid
Display	Power indicator: green LED , Status indicator: red LED
Operating voltage[V]	18...36DC
Switch response time[s]	<1
Maximum power consumption[W]	< 2W
Output	RELAY
Switch output maximum load[mA]	36V(DC)/1A
NO/NC setting	Yes
Learning switching point function	Yes
Medium temperature[°C/°F]	-40...+200/-40...+392
environment temperature[°C/°F]	-40...+85/-40...+185
Operating pressure[bar]	Max. 40 bar
Thread connection	G1/2"A
Probe length[mm]	250
Connection	M12 socket
Housing material	Stainless steel 316L
Probe material	PEEK
Probe material/Wetted Parts	IP67/IP69K*
EMC	ESD 6KV III
	EFT 2KV III
	Surge immunity test 500V I
Walkie talking experiment[mm]	< 5

Dimension[mm]



Panel and M12 Connection	
Drawing	
Note*	Use sanitary adapter to upgrade to IP69K (Optional accessory)



Akdeniz Mekatronik San.Tic.Ltd.Şti
 Yeşiloba Mahallesi 46290 Sk. No:4 Adana/Türkiye
 Tel. +90 322 428 11 44
 E-mail: info@akdenizmekatronik.com.tr