



TA1008 Electronic Temperature Sensors M12 socket Connection: Internal thread M18 x 1.5 Programmable Switching + Analogue output 3 digit display Probe length L=200mm Sensing range -40...150°C -40...302°F	 CE RoHS
Applications	Liquid and gas
Output	NO  /NC  Analogue output 4...20mA, 0...10V
Supply voltage[V]	18...36 DC
Max. overload current[mA]	300
Short-circuit protection	Pulsed
Reverse polarity protection	Yes
Overload protection	Yes
Watchdog	Yes
Voltage drop[V]	<2
Current consumption[mA]	<50
Analogue output	4...20mA(Rmax:5000Ohm);0...10V(Rmin:1000Ohm)
Setting range	
Analogue start point ASP[°C/°F]	-40...140 / -40...284
Analogue end point AEP[°C/°F]	-30...150 / -22...302
Switching point SP[°C/°F]	-39.5...150 / -39...302
Reset point rP[°C/°F]	-40...149.5 / -40...301
In steps of	0.5/1
Programming options	Hysteresis range / Window function, NO / NC Min/Max, Factory reset, °C/°F
Adjustment of switching point	via pushbuttons
Accuracy	
Switching accuracy[°C/°F]	±0.2/±0.36
Analogue accuracy[°C/°F]	±(0.2/0.36+0.4% Measuring range)
Display[°C/°F]	±(0.2/0.36+1/2)
Switching output [°C/°F]	0.5/1
Analogue output[°C/°F]	0.125/0.23
Display[°C/°F]	0.5/1
Temperature drift(/10K)	0.1
Startup delay time[s]	1.5
Measuring/Display cycle[ms]	200

Medium temperature [°C/°F]	-40...150/-40...302
Ambient temperature [°C/°F]	-25...80/-13...176
Storage temperature[°C/°F]	-40...100/-40...212
Insulation resistance[MΩ]	>100 (500V DC)
Protection/Enclosure Rating	IP68
Dimensions[mm]	
ESD[KV]	III
EFT[KV]	III
Walkie talkie experiment[M]	1
Shock resistance[g]	50
Vibration resistance[g]	20
Housing material	Stainless steel 304
Probe material/Wetted Parts	Stainless steel 316L
Function LED/output status	Red LED
Connection	M12 socket
Wiring Core color	
Programming of the output function: Hno= hysteresis / NO Hnc= hysteresis / NC Fno= window function / NO Fnc= window function / NC	