





VS1003 Mini Ultrasonic Level Switch Connection: G1"A Cable entrance: M12 Connector Sensing range: 0.2m...3m Programmable Dual output: Switching output+Analogue output 3 digit display	
Applications	liquid and flat surface objects,ex:wooden plank,glass,paper,plastic sh (*the sensing range of solid decrease with different materials)
Panel Display	3 digital segment + 6×LED
Display Functions	The distance/temperature display can be switched via the buttons
Menu setting	2 buttons
Operating Voltage[V]	20...30 DC
Range[M]	0.2...3
Inactive[M]	≤0.2
Launch angle	<15°
Probe frequency[kHz]	100
Voltage drop[V]	<3.5
Reverse polarity protection	Yes
Overload protection	Yes
Temperature comensation	Yes
Automatic gain control AGC	Yes
Watchdog	Yes
Current consumption[mA]	50
Accuracy/Deviation[%]	±0.1
Minimum Resolution[mm]	3
Output response time[s]	1.5
Output	1x(PNP or NPN) and 1xRelay (4...20mA or 0...10V)
Overload of Analogue output[ohm]	4...20mA,Max (Ub-10V)*50
Overload of switching output[mA]	400
Electric design	NO/NC adjustable
	PNP/NPN adjustable
	SP/RP adjustable
Dimensions[mm]	

Ambient temperature[°C/°F]	-20...70/-4...158
Storage temperature[°C/°F]	-20...70/-4...158
Protection rating	IP68
Resistance[MΩ]	>100(500 VDC)
Shock resistance[g]	20
ESD[KV]	III 6kV
EFT[KF]	III 2kV
Walkie talkie experiment[M]	0.1
Ambient pressure[bar]	<3
Housing material	Stainless steel 316L、PTFE
Probe material	PVDF
Display	
Wiring Core color 	



Akdeniz Mekatronik San.Tic.Ltd.Şti
Yeşiloba Mahallesi 46290 Sk. No:4 Adana/Türkiye
Tel. +90 322 428 11 44
E-mail: info@akdenizmekatronik.com.tr